

TB60L

SPECIFICATION

- Voltage: 12 / 24 VDC
- Max. Load: 6,000 N (Push); 4,000 N (Pull)
- No-Load Speed: 6 ~ 39.5mm/s
- Full-Load Speed: 3.1 ~ 23.4mm/s
- Installation Dimension: S + 163±3mm
- Noise level: ≤52dB
- Option: Hall sensor



PARAMETERS (Note: the current @ 12V is as roughly 2 times as that@ 24V)

CODE	RATED LOAD (N)		RATED CURRENT (A)	RATED SPEED (mm/s)	
	PUSH	PULL		NO LOAD(32VDC)	FULL LOAD(24VDC)
Standard Motor (2600RPM)					
A	6000	4000	3.6	6	3.1
B	5000	4000	3.6	8	4.1
C	3500	3500	3.7	11.9	6
D	2500	2500	3.3	15.9	8.3
E	2000	2000	3.3	21.4	11.1
F	1000	1000	2.2	32.1	19.1
Fast Motor (3400RPM)					
G	6000	4000	4.3	7.6	4.1
H	5000	4000	4.3	10.1	5.4
I	3500	3500	4.7	15.1	7.9
J	2500	2500	4.2	20.2	11.1
K	2000	2000	4.1	27.1	14.9
L	1000	1000	3.1	39.5	23.4

DIMENSION

