

# HTM650

## SPECIFICATION

- **Voltage:** 12/24 VDC
- **Max. Load:** 6,000N ( push); 3,000N ( pull)
- **No-Load Speed:** 5.4 ~ 58mm/s
- **Full-Load Speed:** 2.9 ~ 30mm/s
- **Noise level:** ≤52dB



## PARAMETERS

CODE	RATED LOAD (N)		RATED CURRENT (A)	RATED SPEED (mm/s)	
	PUSH	PULL		NO LOAD(32VDC)	FULL LOAD (24VDC)
<b>Standard Motor (2600RPM)</b>					
A	6000	3000	5	5.4	2.9
B	5000	3000	5	7.1	3.9
C	3000	3000	4.5	11	6.2
D	2500	2500	4	15.8	7.8
E	2000	2000	5	22.5	13
F	1200	1200	4	33	19
G	750	750	4.5	44.5	23.6
<b>Fast Motor(3400RPM)</b>					
I	6000	3000	5	7	3.9
J	5000	3000	5	9.2	4.6
K	3000	3000	4.8	14.6	8.2
L	2500	2500	4.5	21	11
M	2000	2000	4.5	29.2	16
N	1200	1200	5	43.5	23
O	750	750	4.5	58	30

## DIMENSION

